

GLOBAL *Shine*

Colour your world...!

PRODUCT CATALOGUE

SUPERIOR RANGE OF
DECORATIVE PRODUCTS





ABOUT US

GLOBAL SHINE PAINTS PVT. LTD. has come a long way since it since in 2020 . It was started As a firm by Founder Mr MANISH KUMAR who were willing to take on the most trusted, famous and biggest brands of India. Over the course of 5 years GLOBAL SHINE PAINTS became corporate force and one of India's most trusted brands. Today it is worth 20 times of what we start adenoidally. The ambitious project of 'GLOBAL SHINE PAINTS' rests on solid grounds of infrastructure and supply Chain management. It has set up its indigenous state-of-the-art production plant at ALWAR ,(Rajasthan), PATNA (BIHAR). Laced with high precision equipment, this manufacturing unit has an output capacity of 20,000 MT/KL per annum.

Modern automatic machines and advanced Research & Development laboratories labels every GLOBAL SHINE PAINTS product with high quality standards that guarantees ultimate customer satisfaction. Supporting the technical efficiency is the Present stock availability of 6 sales Depots and 42 DISTRIBUTOR'S POINT. These product stock stations prove highly effective in the distribution channel. They enable smooth and uninterrupted supply of 'GLOBAL SHINE PAINTS' products throughout the massive network of 300 dealers & distributors of GLOBAL SHINE spread across India. Making its presence felt in the market 'GLOBAL SHINE PAINTS' is available in a wide range of decorative paint products that like Exterior & Interior Emulsions, Cement Paints, Water based Primers, Acrylic Distempers, Synthetic & GP Enamel, Solvent based Primers, Wood Finishes and Aluminum Paints and Stainer . Whatever may be the surface area, we have all the best colors solutions for you.

OUR VISION

GLOBAL SHINE PAINTS PVT. LTD. and Home Improvements, home of the "Hassle-Free"experience. At Mission, we pride ourselves on the best & highest quality painting services you'll find from any painting company in Over land Park. That's why we guarantee you a hassle-freeexperience with no surprise. We've won Angie's List's Super Service Award every year possible. Tired of the uncertainty of hiring a local painter? No matter whether you're in need of interior painting, exterior painting, or just general home painting services, at Mission we will get your home painting project

done right, on time, and on budget, guaranteed. At Vision Painting, we strive to achieve total customer satisfaction. We accomplish this with superb service, high quality work, and a team that is committed to meeting budgets and time lines. We understand and accommodate to each client and their specific needs. Over the years, we have completed thousands of successful commercial and residential projects and have become Indianapolis's favourite painting and drywall contractor. The common thread is integrity, professionalism, and attention to detail. We are committed to hiring and retaining the most competent staff. Our people make the difference and we are proud to show you why Vision Painting has earned such great a great reputation.

OUR MISSION

- We are committed to be the best organization among building material manufacture.
- Customer Relationship and satisfaction is our prime duty and responsibility.
- Moving a step towards.
- Retail profit & customer retention.
- Customer quality Satisfaction.
- Painter Relationship, profit and satisfaction.
- Maintaining of Corporate social responsibility.

PearlauraTM ADVANCE

HI-SHEEN LUXURY INTERIOR EMULSION SMOOTH WALL FINISH

LEVEL
APCOLITE
EMULSION

Pearl Aura Advance Hi-Sheen Luxury Interior Emulsion is made with the high class technology that gives you superior features and a wide array of color choice.

METHOD OF APPLICATION

SURFACE PREPARATION: First of all prepare a surface free from all waterproofing issues. Surface must be free from dirt, dust, algae/fungi & loose flaking paint etc.

PUTTY (If Required): Apply a thin coat of Aqua Walltech Wall Putty to fill any dents & cracks or to smoothen the surface. Allow it to dry for 6-8 hrs.

PRIMING: Apply a coat of "Global Interior Wall Primer" by thinning with potable water and allow it to dry for 4-6 hrs.

APPLICATION: Apply 2-3 coats of "Pearl Aura Interior Emulsion" by thinning with potable water 40% by volume. Maintain a gap of 4-6 hrs between coats. Avoid excess dilution for better performance.



FUNGUS &
WATER
RESISTANCE



FAST
DRYING &
EXTRA SHINE



EXCELLENT
HIDING
CAPACITY



HIGH
COVERAGE &
SMOOTH FINISH

PACK SIZE 01Ltr. 04Ltr. 10Ltr. 20Ltr.

Colour Variants available with extra cost.



PearlauraTM

INTERIOR EMULSION SMOOTH WALL FINISH

LEVEL
TRACTOR
EMULSION

Pearl Aura Interior Emulsion is made with the high class technology that gives you superior features and a wide array of color choice.

METHOD OF APPLICATION

SURFACE PREPARATION: First of all prepare a surface free from all waterproofing issues. Surface must be free from dirt, dust, algae/fungi & loose flaking paint etc.

PUTTY (If Required): Apply a thin coat of Aqua Walltech Wall Putty to fill any dents & cracks or to smoothen the surface. Allow it to dry for 6-8 hrs.

PRIMING: Apply a coat of "Global Interior Wall Primer" by thinning with potable water and allow it to dry for 4-6 hrs.

APPLICATION: Apply 2-3 coats of "Pearl Aura Interior Emulsion" by thinning with potable water 40% by volume. Maintain a gap of 4-6 hrs between coats. Avoid excess dilution for better performance.



EXTRA
BRIGHT &
HIGH COVERING



ANTI FUNGUS
& HIGH
COVERING



EXCELLENT
HIDING
CAPACITY



DUST PROOF
& ECO FRIENDLY

PACK SIZE 01Ltr. 04Ltr. 10Ltr. 20Ltr.

Colour Variants available with extra cost.





Rang VilasTM ADVANCE

WEATHER GUARD EXTERIOR EMULSION HD MATT FINISH

LEVEL
APEX
EMULSION

Rang Vilas Advance Weather Guard Exterior Emulsion is a Luxury Quality with the state of art technology having smooth and uniform wish which is used to give the excellent and beautiful colours to your exterior walls.

METHOD OF APPLICATION

RFACE PREPARATION: First of all prepare a surface free from all waterproofing issues. Surface must be free from dirt, dust, algae/fungi & loose flaking paint etc.

PUTTY (If Required): Apply a thin coat of Aqua Walltech Wall Putty to fill any dents & cracks or to smoothen the surface. Allow it to dry for 6-8 hrs.

PRIMING: Apply a coat of "Global Interior Wall Primer" by thinning with potable water and allow it to dry for 4-6 hrs.

APPLICATION: Apply 2-3 coats of "Rang Vilas Emulsion Exterior Emulsion" by thinning with potable water 40% by volume. Maintain a gap of 4-6 hrs between coats. Avoid excess dilution for better performance.



WATER
RESISTANCE



FAST DRYING
& HIGHER
COVERING



DUST PROOF
& ECO FRIENDLY

PACK SIZE 01Ltr. 04Ltr. 10Ltr. 20Ltr.

Colour Variants available with extra cost.



Rang VilasTM

WEATHER PROOF EXTERIOR EMULSION HD MATT FINISH

LEVEL
ACE
EMULSION

Rang Vilas Emulsion is a premium quality with the state of art technology having smooth and uniform wish which is used to give the excellent and beautiful colours to your exterior walls.

METHOD OF APPLICATION

RFACE PREPARATION: First of all prepare a surface free from all waterproofing issues. Surface must be free from dirt, dust, algae/fungi & loose flaking paint etc.

PUTTY (If Required): Apply a thin coat of Aqua Walltech Wall Putty to fill any dents & cracks or to smoothen the surface. Allow it to dry for 6-8 hrs.

PRIMING: Apply a coat of "Global Interior Wall Primer" by thinning with potable water and allow it to dry for 4-6 hrs.

APPLICATION: Apply 2-3 coats of "Rang Vilas Emulsion Exterior Emulsion" by thinning with potable water 40% by volume. Maintain a gap of 4-6 hrs between coats. Avoid excess dilution for better performance.



SUPERIOR
BRIGHTNESS



SUPER SMOOTH
& MATT FINISH



EXCELLENT
HIDING
CAPACITY



HIGHEST
COVERING &
WEATHER
GUARD

PACK SIZE 01Ltr. 04Ltr. 10Ltr. 20Ltr.

Colour Variants available with extra cost.



TEJAS Glow

INTERIOR EMULSION SMOOTH WALL FINISH

LEVEL
TRACTOR SPARC

Tejas Glow Interior Emulsion is made with the high class technology that gives you superior features and a wide array of color choice.

METHOD OF APPLICATION

SURFACE PREPARATION: First of all prepare a surface free from all waterproofing issues. Surface must be free from dirt, dust, algae/fungi & loose flaking paint etc.

PUTTY (If Required): Apply a thin coat of Aqua Walltech Wall Putty to fill any dents & cracks or to smoothen the surface. Allow it to dry for 6-8 hrs.

PRIMING: Apply a coat of "Global Interior Wall Primer" by thinning with potable water and allow it to dry for 4-6 hrs.

APPLICATION: Apply 2-3 coats of "Tejas Glow Interior Emulsion" by thinning with potable water 40% by volume. Maintain a gap of 4-6 hrs between coats. Avoid excess dilution for better performance.

**1 YEARS
WARRANTY***



FAST
DRYING
SKILL



EXCELLENT
HIDING
CAPACITY



HIGH
COVERAGE



VALUE FOR
MONEY

PACK SIZE 01Ltr. 04Ltr. 10Ltr. 20Ltr.

Colour Variants available with extra cost.



Spot light

PREMIUM QUALITY EXTERIOR EMULSION HD MATT FINISH

LEVEL
ACE SPARC

Rang Vilas Exterior Emulsion is a premium quality with the state of art technology having smooth and uniform finish which is used to give the excellent and beautiful colours to your exterior walls.

METHOD OF APPLICATION

SURFACE PREPARATION: First of all prepare a surface free from all waterproofing issues. Surface must be free from dirt, dust, algae/fungi & loose flaking paint etc.

PUTTY (If Required): Apply a thin coat of Aqua Walltech Wall Putty to fill any dents & cracks or to smoothen the surface. Allow it to dry for 6-8 hrs.

PRIMING: Apply a coat of "Global Interior Wall Primer" by thinning with potable water and allow it to dry for 4-6 hrs.

APPLICATION: Apply 2-3 coats of "Rang Vilas Emulsion Exterior Emulsion" by thinning with potable water 40% by volume. Maintain a gap of 4-6 hrs between coats. Avoid excess dilution for better performance.

**1 YEARS
WARRANTY***



SUPER
SMOOTH
FLOW



PURE
BRIGHT
FINISH



EXCELLENT
HIDING
CAPACITY



HIGH
COVERAGE

PACK SIZE 01Ltr. 04Ltr. 10Ltr. 20Ltr.

Colour Variants available with extra cost.





1 YEARS WARRANTY



FAST DRYING SKILL



EXCELLENT HIDING CAPACITY



HIGH COVERAGE



VALUE FOR MONEY

PACK SIZE 01Ltr. 04Ltr. 10Ltr. 20Ltr.

Colour Variants available with extra cost.

ALLⁱⁿOne

LEVEL
LUXURY EMULSION

INTERIOR & EXTERIOR EMULSION UNIVEREAL SUPERIOR TOPCOAT

All in One Universal Emulsion is made with the high class technology that gives you superior features and a wide array of color choice.

METHOD OF APPLICATION

SURFACE PREPARATION: First of all prepare a surface free from all waterproofing issues. Surface must be free from dirt, dust, algae/fungi & loose flaking paint etc.

PUTTY (If Required): Apply a thin coat of Aqua Walltech Wall Putty to fill any dents & cracks or to smoothen the surface. Allow it to dry for 6-8 hrs.

PRIMING: Apply a coat of "Global Wall Primer" by thinning with potable water and allow it to dry for 4-6 hrs.

APPLICATION: Apply 2-3 coats of "All in One Emulsion" by thinning with potable water 40% by volume. Maintain a gap of 4-6 hrs between coats. Avoid excess dilution for better performance.



Hi PERFORMANCE WARRANTY



SUPER SMOOTH



EXTRA SHINE



LOW VOC & VALUE FOR MONEY



HIGHEST COVERAGE

PACK SIZE 01Kg. 02Kg. 05Kg. 10Kg. 20Kg.

Colour Variants available with extra cost.

COLOR^{Smith}

LEVEL
TRACTOR UNO

ACRYLIC WASHABLE DISTEMPER SMOOTH WALL FINISH

Color Smith Acrylic Distemper is a water based interior wall paint. It is the best quality acrylic distemper which gives the walls a smooth and delightful matt finish that lasts for ages. A tested formulation of acrylic co-polymers binders used to give unmatched performance. It also comes in a wide range of attractive shades.

METHOD OF APPLICATION

SURFACE PREPARATION: First of all prepare a smooth and uniform surface. This can be done by scraping the old painted surface and removing the flaking particles and all the dirt or dust which is present on the surface.

PUTTY: Make the surface smooth by applying minimum two coats of "Aqua Walltech Wall Putty" allow the surface to dry for 6-8 hours. Rub the surface with emery paper 180 no. To further smoothen the surface.

APPLICATION: Apply one coat of "Water Thinnable Cement Primer". Take 1 Kg. of "Global Paints ColorSmith Acrylic Distemper" and Add 500- 600 mL of water to make it thin for brushability and apply the first coat.

Apply the second coat after an interval of 6-8 hours





NXONE

INTERIOR WALL PRIMER SUPERIOR SMOOTH BASECOAT

LEVEL
TRUE CARE

NXONE is a water base interior primer which gives a protective undercoat with alkali resistant property. It is suitable for interior plastered, masonry, POP or pre painted surfaces. It is specially formulated to give excellent adhesion to all interiors

METHOD OF APPLICATION

SURFACE PREPARATION: First of all prepare a smooth and uniform surface. This can be done by scraping the old painted surface and removing the flaking particles and all the dirt or dust which is present on the surface.

MIXING: Stir and strain the material before using it, Now thin the primer with 25% to 30% of clean water by volume, but don't over-thin. Apply at least 2-3 coats for smooth finish with Brush or Roller.

APPLICATION: A brush, roller can be used to apply Global Paints NXONE Interior Primer". The equipment should be washed after use.

RECOATING: Let the coat dry, Leave for 2 to 4 hour, then apply another coat



PACK SIZE 01Ltr. 04Ltr. 10Ltr. 20Ltr.

Colour Variants available with extra cost.



NXONE

EXTERIOR WALL PRIMER SUPERIOR BASECOAT

LEVEL
TRUE CARE

NXONE is a water base exterior primer which gives a protective undercoat with alkali resistant property. It is suitable for interior plastered, masonry, POP or pre painted surfaces. It is specially formulated to give excellent adhesion to all exteriors

METHOD OF APPLICATION

SURFACE PREPARATION: First of all prepare a smooth and uniform surface. This can be done by scraping the old painted surface and removing the flaking particles and all the dirt or dust which is present on the surface.

MIXING: Stir and strain the material before using it, Now thin the primer with 25% to 30% of clean water by volume, but don't over-thin. Apply at least 2-3 coats for smooth finish with Brush or Roller.

APPLICATION: A brush, roller can be used to apply Global Paints NXONE Exterior Primer". The equipment should be washed after use.

RECOATING: Let the coat dry, Leave for 2 to 4 hour, then apply another coat



PACK SIZE 01Ltr. 04Ltr. 10Ltr. 20Ltr.

Colour Variants available with extra cost.





NXONE

All in One Interior & Exterior Wall Primer

LEVEL
DECO PRIME

MULTI SURFACE

Nxone All in One Primer provides the excellent features like superior filling property, Alkaline resistant and good adhesion. It makes walls protected against fungi, Algae, dampness caused by lashing rain water.

METHOD OF APPLICATION

SURFACE PREPARATION: First of all prepare a smooth and uniform surface. This can be done by scraping the old painted surface and removing the flaking particles and all the dirt or dust which is present on the surface.

MIXING: Stir and strain the material before using it, Now thin the primer with 25% to 30% of clean water by volume, but don't over-thin. Apply at least 2-3 coats for smooth finish with Brush or Roller.

APPLICATION: A brush, roller can be used to apply Global Paints NXONE All in One Primer". The equipment should be washed after use.

RECOATING: Let the coat dry, Leave for 2 to 4 hour, then apply another coat



PACK SIZE 01Ltr. 04Ltr. 10Ltr. 20Ltr.

Colour Variants available with extra cost.



AQUA walltech™ WALL PUTTY

LEVEL
**INDIA'S BEST
WALL PUTTY**

WHITE CEMENT BASE PUTTY

Aqua Walltech Wall Putty is a water resistant white cement and polymer based putty which provides a strong base on concrete (internal and external) and ceilings. It is applied before painting of the wall. It fills the ne pores of the walls and ceiling thereby providing a white smooth and dry surface for painting. Being water resistant it provides a protective base which prevents expensive paints from falling.

Aqua Walltech White Cement Wall Putty has special added polymers provides a strong base ensuring a longer life for the painted surface.



PACK SIZE 05 Kg. 20 Kg. 40 Kg.

Waterproof and acrylic putty available with extra cost.





COLORSmith

CEMENT PAINT

INTERIOR & EXTERIOR

Color Smith is one of the best "Whitest White Cement" It heGss in developing a pristine white canvas for crafting architectural elegance. It's the key ingredient in the application of decorative cement paints, mosaic tiles, terrazzo floorings and marble laying. Its remarkably high refractive index and high opacity imparts a gleaming luster and smooth finish to surfaces.

Besides, it's also a significant constituent in wall finishes such as Grit Wash, Stone crete and Tyrolean



EXCELLENT
ADHESION



COLOR
VARIETY
AVAILABLE



MULTI
PURPOSE
USE



QUICK DRYING
CAPACITY

PACK SIZE 20Kg. 25Kg.

Colour Variants available with extra cost.



AQUA walltech™

TILE ADHESIVE

INTERIOR & EXTERIOR

TILE & STONE EXPERT POLYMER MODIFIED

POLYMER MODIFIED ADHESIVE TO FIX MARBLE SLABS & MOSAIC,
STONE & TILE ON INTERNAL & EXTERNAL WALLS & FLOOR SURFACES.



NON SLIP



NO
HOLLOW
SOUND



POLYMER
MODIFIED

PACK SIZE 20Kg.





AQUA walltech™

WHITE CEMENT WHITE WASH DECORATIVE

Color Smith is one of the best "Whitest White Cement" It in developing a pristine white canvas for crafting architectural elegance. It's the key ingredient in the application of decorative cement paints, mosaic tiles, terrazzo floorings and marble laying. Its remarkably high refractive index and high opacity imparts a gleaming luster and smooth finish to surfaces.

Besides, it's also a significant constituent in wall finishes such as Grit Wash, Stone crete and Tyrolean



EXCELLENT
ADHESION



COLOR
VARIETY
AVAILABLE



MULTI
PURPOSE
USE



QUICK DRYING
CAPACITY

PACK SIZE 50Kg. 25Kg. 5Kg. 1Kg.

Colour Variants available with extra cost.



COLOR Plus

UNIVERSAL STAINER

INTERIOR & EXTERIOR

A universal stainer is a concentrated liquid pigment added to base paints, such as emulsions, distempers, and enamels, to create custom colors or intensify existing shades. You mix a small amount of the high-pigment stainer into a larger volume of base paint to achieve the desired hue. The process involves shaking the stainer, adding the desired amount (typically a small percentage, like 5% by volume), and then thoroughly mixing it with the paint to ensure a uniform, streaking-free color



HIGH
STRENGTH



INTER
MISCIBLE








LIGHT FAST
PIGMENT





PACK SIZE 200ml 100 ml 50ml




EMULSIONS SHADES

					
Beacon Gs3109	Magnolia Gs0387	Tinge of Rose Gs8084	Sky Mimic Gs7420	Cashmere-N Gs3119	Autumn Day Gs8252
					
Summer Dew Gs7867	Orange Frost Gs7978	Romance Gs0010	Alliance Gs1203	Green Whisper Gs2425	Crusade-N Gs0684
					
Wild Yellow Gs7865	Corel Beach Gs7969	Baby Blush Gs8138	Bali Blue Gs8266	Paddy Field Gs7570	Steel Gs6142
					
Sunlit Sand Gs7896	Martian Sky Gs7952	Candy Gs0478	Summer Sky Gs7274	Forest Hike Gs7625	Grey Flannel Gs8331
					
Tons of Sun Gs7895	Orange Spark Gs7951	Rosy Coral Gs8031	Gauguin Blue Gs7344	sultry Gs9383	Aluminium Gs8337
					
Sporty Yellow Gs0104	Orange Appeal Gs7949	Sunrise Gs0526	Piece of Sky Gs7304	Green Gold Gs0342	Smoke-N Gs0616
					
Mustard Field Gs0102	Glorious Sunset Gs0111	Rodeo Gs0117	Smooth Sapphire Gs7236	Mehendi-N Gs2361	Stone Path Gs8255

DISTEMPER SHADES

		
Pale Cream Gs184	Ivory Gs826	Daffodil Gs3503
		
Meripink Gs5802	Promise Gs827	Pale Rose Gs0421
		
Pastel Green Gs2593	Light Green Gs2595	Aquamarine Gs2594
		
Deep Aqua Gs2596	Wile Lilac Gs1479	Electric Blue Gs1478

COLOURS COMBINATIONS

	
Bashful Beige Gs8002 Morning Frost Gs7361	Hushed Hue Gs7541 Lemon Souffle Gs7773
	
Sand of Time Gs7771 Nut Brown N Gs7665	Farm Land Gs9532 Light Ochre Gs7926
	
Aqua Hint Gs7160 Mystic Dream Gs7804	Dew Drop Gs0299 Corel Radiance Gs2015
	
Apricot Illusion Gs7160 Sunrise Gs7554	Ivory Gs2015 Milan Red Gs8809

OUR UPCOMING PRODUCTS

TARPIN OIL

LIQUID
WATERPROOFING
COMPOUND

SYNTHETIC ENAMEL

RED OXIDE PRIMER

WOODEN
PRIMER PSW

BLACK JAPAN

EPOXY GROUT
&
TILE GROUT

METALLIC PAINT



Introducing
NG NEXT
GENERATION
PRODUCTS



Global Shine Paints (P.) Ltd

H.O. : TSE-41, Office Suite, Gaur City Mall, Techzone-IV, Greater Noida- 201306 (UP)
Unit-II: Plot No. 38, Khata 45, Mandi Bypass, Patna-80009 (Bihar)
E-mail : care@globalshinepaints.com, Website: www.globalshinepaints.com

CUSTOMER CARE: +91-8800-98-0871, 8800-98-0241



HERO: 981162503